

- Best Design
- Excellent Quality
- Out Standing Capability

PEBCO COMNET 8900 G

CASH RECYCLING

Multi function ATM for Global Business

Seize the Spotlight!

Chungho ComNet provides the most reliable, versatile and cost effective ATM. Our next generation cash recycling machine, the **ComNet 8900G** is designed to create efficient self service with fully advanced functions. It has bright features, outstanding capabilities and excellent qualities. **ComNet 8900G** is now in the center stage as a new feature of global business.



Reliability

Designed with technology and deep understanding of our customer's needs, the **ComNet 8900G** can offer outstanding quality standards and reputation for excellent value.

Security

With its UL291 level 1 cabinet, PCI Certified EPP, security camera and anti-skimming EMV card reader, the **ComNet 8900G** is equipped for the highest level protection.

High Capacity

the **ComNet 8900G** manages large capacities of cassettes and high transaction volumes. It is Configured with 4 denominations with capacities for up to 3,000 notes each cassettes and a receipt printer for 5,000 transactions.

Customization

Our **ComNet 8900G** technology can support future compliance and application needs in the banking industry by offering various options based on the customer's specific needs.

PEBCO COMNET 8900 G

CASH RECYCLING

Multi function ATM for Global Business



Specification

CUSTOMER HANDLING UNIT

Display	15" TFT Color LCD with 8 Metal Function Keys (Resolution 1024 X 768)
Keyboard	Encryption Pin Pad (4 X 4 numeric keys) with PCI 2.X compliant
Card Reader	Motorized Card Reader (EMV, PBOC Approved)

CONTROL UNIT & SYSTEM

CPU	Intel Core 2 Duo 2.93GHz or above
Memory	DDR3 2GB or above
Storage	500G HDD or above
Media	DVD - ROM, (Optional: DVD-Multi)
O/S	Windows XP
Interface	TCP/IP (LAN) or Optional Dial-up Modem, X.25, Wireless

CASH RECYCLING UNIT

Cassette Capacity	Recycle: 10,800 Notes (2,700 per Cassete)
Number of Cassette	NonRecycle: 12,000 Notes (3,000 per Cassete)
Type	Pocket shutter Type
Speed	8 notes/sec
Reject Box	Reject (1,800 notes), Reteact (200 notes)

RECEIPT PRINTER

Method	Thermal Printer
Paper Setting	Semi-auto loading method
Speed	Max. 150 mm/sec
Paper Width	80 mm
Receipt Capacity	5,000 transactions

JOURNAL PRINTER(Optional)

Method	Thermal Printer
Speed	Max. 150 mm/sec
Paper Width	80 mm
Receipt Capacity	5,000 transactions

SECURITY

Cabinet	UL 291 Level 1, GBA Compliant
Lock	Singel or Dial Lock (Dial Lock, Electronic Lock, Long Key)

PHYSICAL

Maintenanc Access	Front / Rear Access
Dimension (WxHxD)	566 mm x 945 mm x 1,428 mm (Front), 566 mm x 995 mm x 1,428 mm (Rear)
Weight	Approx. 600 kg

OPERATING ENVIRONMENT

Temperature	Indoor 10~32 ℃, ITW 0~40 ℃
Humidity	20~80%
Power Supply	AC100 - 240V, 50/60Hz

APPLICATION SOFTWARE

XFS (Extensions for Financial Services)
NDC (NCR Direct Connect)
DDC (Diebold Direct Connect)

OPTIONS

ITW (Through The Wall) Kit	Heater
Privacy Film	Customer Detective Sensor
Touch Screen	ADA Compliant
Barcode Reader	Security Camera (Face, Hand)
Contactless RF Card Reader	DVR

Head Office: PEBCO Building, No. 19, Mohebi St., Northern Sohrevardi Ave.,
Tehran - IRAN +98 21 8817 3000

Factory: 19th St., Maadiran Sq., Hashtgerd Ind. Zone, Hashtgerd, Karaj - IRAN
www.brg-pebco.com **info@brg-pebco.com**