

- Best Design!
- Excellent Quality!
- Outstanding Capability!



PEBCO 8850-TTW

Seize the Spotlight!

Pardakht Electronic Behestan Co. (PEBCO Electronics) provides the most reliable, versatile and cost effective models. Our next generation cash dispenser, the PEBCO-COMNET 8850-TTW in partnership with South Korea Chungho comnet Co. is designed to create efficient self service with fully advanced functions. It has bright features, outstanding capabilities and excellent qualithes. The PEBCO-COMNET 8850-TTW is now in the center stage as a new feature of global business.

Reliability

Designed with key technology and deep understanding of our customers' needs, the PEBCO-COMNET 8850-TTW can offer outstanding quality standards and reputation for exellent value.

Security

With its UL291 level 1 cabinet, PCI Certified EPP, security camera and anti-Skimming EMV card reader, the PEBCO-COMNET 8850-TTW is equipped for the highest level protection.

High Capacity

The PEBCO-COMNET 8850-TTW manages large capacities of cassettes and high transactions volumes. It is configured with 4 denominations with capacities for up to 3,000 notes for each cassette.

Customization

Our PEBCO-COMNET 8850-TTW Series technology can support future compliance and application needs in the banking industry by offering various options based on customers' specific needs.















Specification

Specification	
CUSTOMER HANDLING	
Display	15.0" TFT Color LCD with 8 Metal Function Keys (Resolution 1024 x 768)
Keyboard	Encryption Pin Pad (4 x 4 numeric keys) with PCI 2.X Compliant
Card Reader	Motorized Card Reader (EMV, PBOC, Approved)
CONTROL UNIT & SYSTE	M
CPU	Dual Core, 3.10 GHz
Memory	DDR3 2G
Storage	500G SATA HDD
Media	DVD - ROM
OS	Windows Pos Ready
Interface	TCP/IP (LAN) or Optional Dial-up Modem, Wireless
CASH DISPENING	
Cassette Capacity	3.000 Notes per Cassete
Number of Cassette	Up to 4 Cassette
Туре	Present Type
Speed	7 notes / sec
Reject Box	Capacity Approx 300 Bills
RECEIPT PRINTER	
Method	Direct Thermal Line Printer
Paper Setting	Semi-auto loading method
JOURNAL PRINTER	
Method	Direct Thermal Line Printer
Paper Setting	Semi-auto loading method
SECURITY	
Cabinet	UL 291 Level-1, GBA Compliant
Lock	Electric Lock, Long Key Lock
PHYSICAL	
Maintencance Access	Rear Access
Dimension (WxHxD)	506 x 1433 x 845 (mm)
Weight	Approx, 450 kg, 4-cartridge CDU, including options, bill & media
OPERATING ENVIRONM	ENT
Temperature	Indoor 10~32°C / TTW 0~40°C
Humidity	20~85%
Power Supply	AC100 - 240V, 50/60Hz
APPLICATION SOFTWAR	
	CEN/XFS Support
	NDC Support
	DDC Support
INSTALLED ADDITIONAL	
	Bar Code (1D)
	TTW (Through the wall) Kit
	Camera (Face, Hand)
	1 1

Head Office: PEBCO Building, No. 19, Mohebi St., Northern Sohrevardi Ave., Tehran - IRAN +98 21 8817 3000

Factory: 19th St., Maadiran Sq., Hashtgerd Ind. Zone, Hashtgerd, Karaj - IRAN www.brg-pebco.com info@brg-pebco.com